



Technical Specification / Data Sheet

Product: LBS Vista Sliding Grilles

Supplier

LBS Group, Unit 6, Sterling Trading Estate, Rainham Road South, Dagenham, Essex RM10 8TX
T: 020 8517 6655 F: 020 8984 0378 E: sales@lbsgroup.co.uk W: www.lbsgroup.co.uk

Application

A manual sliding grille in a variety of design options for medium to low security. Designed to provide physical protection of shopfronts, servery's and bar areas for internal situations, for example shopping malls.

Size

No maximum width: Maximum height 4800mm (varies by design)

Arrangement

Top running manual operated sliding grilles that can collapse into discreet pockets. Not restricted to straight lines, they can curve & even turn 90°. Can either bunch one side or bi-part, this can be an equal or unequal split.

Top Track

38mm x 45mm aluminium top track with joining pins & plates. Curves are standard 45° or 90°, but custom curves are available (subject to performance limitations).

Locking

There are many locking options available & these would be determined by on the site conditions & requirements. These include hook lock slam posts & top/bottom espagnolette locking with discreet dust capped sockets.

Curtain

Available in many different styles & patterns including: Portcullis type grilles, solid or with perforated aluminium, glass or polycarbonate infills.

Finish

Standard: clear anodized. Stock colours Black, White or Medium Bronze
Additional RAL & custom colours available

Operation

Manual

Stacking

Approximately 170mm per metre (depending on the amount of locking posts)

Options

Eight different curtain types

Doc: LBS Vista

